

The following reference signs mentioned in the description have now been added to the formal drawings. (See marked up copy of the drawings as filed with changes marked in red, and clean copy of new formal drawings, enclosed).

Distal end 27 (See FIG. 4A , 4B, 5C, 6A and 6B) and Paragraph [0034].

Frame portion 15 (See FIG. 1 and 2) and paragraph [0028] and [0029].

Lower end 42 (See FIG. 4A, 4B, 6B) and paragraph [0035].

Upper portion 44 (See FIG. 4A, 4B, 6B) and paragraph [0036].

Distal end 68 (See FIG. 4B) and paragraph [0059].

Indicia 31 (See FIG. 1, 2) and paragraph [0042].

Vinyl material 36 (See FIG. 1, 2) and paragraph [0042].

First and/or second rigid member 34, 35 (See FIG. 3) and paragraph [0044].

Opposing sides 38, now 38A and 38B (See FIG. 3) and paragraph [0044].

Light fixture 84 (See FIG. 2) and paragraph [0062].

Multiple points of light 89 (See FIG. 9A) and paragraph [0062].

The following reference sign(s) have been added to the specification and/or drawings for clarity: lower portion 93 (See FIG. 3) and paragraph [0062].

Upper portion 94 (See FIG. 3) and paragraph [0062].

Inner side of first vertical member 95 (See FIG. 3) and paragraph [0062].

Inner side of second vertical member 96 (See FIG. 3) and Paragraph [0062].

Releasable securement means 33 (See FIG. 4A, 4B) and Paragraph [0043].

Threaded bolt 67 and Nut 45 (See FIG. 4B) and Paragraph [0048].

Distal end 65 of clamping arm (See FIG. 4A, 4B) and Paragraph [0035].

Pivot Aperture 79 (See FIG. 4B, 7C and 7F) and Paragraph [0048].

As previously noted, the drawings as originally filed have changes marked in red. New Corrected formal drawings are enclosed, in compliance with 37 CFR 1.121(d).

The specification has been amended to more clearly claim applicant's invention, in accordance with the drawings and specification as originally filed. See copy of amended specification and clean copy of the amended specification, enclosed.

Paragraph [0062] of the specification has been amended to include a light string 8Z, to comply with drawing 9B as originally filed.

Paragraph [0037] of the specification has been amended to add: The clamping arm is preferably offset at least four inches inward of the opposing ends to avoid obstacles located beneath the table top. This terminology is found in claim 9, as originally filed, and has been incorporated into the specification to provide antecedent basis.

Opposing sides 38 has been amended in the drawings FIG. 3 and specification in paragraph [0044] and [0045] to read, opposing sides 38A and 38B, for clarity.

Paragraph [0048] has been amended in line 1-2, following "pivotally secured 48", to read with a threaded bolt 67 and nut 45. The bolt head 48 is clearly shown in FIG. 4B as originally filed.